



Date of issue : 05/01/2005

Last. mod. date : 28/07/2008

Product code**02817 RI-500/40 MATT SILVER TC AP 905 WKPE 150****Description**

Matt solid aluminium foil, top coated for good printability.

Printable in solvent based screenprinting.

Super permanent acrylic adhesive, with excellent water, steam and temperature resistance. Very good UV resistance.

Nameplates, industrial instruction labels for electrical appliance and motors, with very good temperature resistance. Very good water resistance. The labels can be easily debossed using typewriters or a variety of lettering machines.

Technical data**FACE MATERIAL**

Type	TC Aluminium foil
Colour and Finish	Aluminium, matt
Weight	110g/m ²
Thickness	40μ

ADHESIVE

Reference	AP 905
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-40°C/+120°C
Shear	Very High
Tack FTM9	15N/inch ²
FinAdh FTM2	12N/inch

RELEASE BACKING

Type	1 side silicone coated 2 side PE coated kraft
Colour and Finish	White
Weight	144g/m ²
Thickness	166μ

CHEMICAL RESISTANCE

Detergent	No effect (24 Hrs)
Gasoline	No effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% HCl	No effect (10 min)
10% NH4OH	No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.